



## Dell PowerSwitch S3248T-ON

48-port switch for data center management.

The S3248T-ON offers power-efficient and resilient 1GbE switching solution for advanced Layer 3 distribution with integrated 10GbE SFP+ and 100GbE QSFP28 ports. The S3248T-ON has high-performance capabilities and wire-speed performance utilizing a non-blocking architecture to easily handle unexpected traffic loads. Use dual internal hot-swappable 80PLUS Platinum certified power supplies for high availability and power efficiency.

### Modernize network architectures

S3248T-ON supports VRF Lite, allowing it to be partitioned into multiple virtual routers with isolated control and data planes on the same physical switch.

### Deploy with confidence at any scale

S3248T-ON helps create performance assurance with a data rate up to 576Gbps (full duplex) and a forwarding rate up to 800Mpps.

Dell's ProSupport Infrastructure Suite is available for enterprise-class support that aligns with the criticality of your systems, the complexity of your environment, and how you allocate your IT resources.

### Hardware, performance and efficiency

- 1U switch with 48 line-rate RJ45 1GbE ports, and four integrated 10GbE SFP+ ports.
- Two 100GbE QSFP28 uplink ports.
- Add a second 80PLUS Platinum certified hot swappable internal power supply.
- Variable speed fan operation helps decrease cooling and power costs.
- Energy-efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Dell Fresh Air compliance for operation in environments up to 113°F (45°C) reduces cooling costs.


### Deploying, configuring and managing

- OpenConfig gNMI interface for system management.
- Private VLAN extensions and Private VLAN Edge support.
- AAA authorization, TACACS+ accounting and RADIUS support for comprehensive secure access support.
- Achieve high availability and full bandwidth utilization with MLAG and support firmware upgrades without taking the network offline.
- Layer 3 Advanced IPv4 and IPv6 functionality including BGP, VRF, BFD, PIM-SSM, IGMP, OSPFv2/v3
- VXLAN support



S3248T-ON rear image. PSU to IO airflow displayed.

Product	Description
S3248T-ON	<ul style="list-style-type: none"> <li>S3248T-ON IO/PS Airflow: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2x 100G QSFP28 ports, 1x 550W AC PSU included</li> <li>S3248T-ON PS/IO Airflow: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x 10G SFP+ ports, 2x 100G QSFP28 ports, 1x 550W AC PSU included</li> </ul>
Dell SW Configurations	Dell SmartFabric OS10 Enterprise SONiC Distribution by Dell Technologies
Power cords	C13 to NEMA 5-15 C13 to C14
Power supplies (optional)	<ul style="list-style-type: none"> <li>550W AC hot swappable with IO/PS airflow, adds redundancy to S3248T-ON</li> <li>550W AC hot swappable with PS/IO airflow, adds redundancy to S3248T-ON</li> <li>550W DC hot swappable with IO/PS airflow, adds DC power</li> <li>550W DC hot swappable with PS/IO airflow, adds DC power</li> </ul>
Optics, Cables and Cable Management	Please refer to <a href="#">Dell Networking Transceivers and Cables spec sheet</a> for complete list of optics and cables.
Fans (spare)	Fan module, IO to PSU Airflow Fan module, PSU to IO Airflow

Technical specifications		
<p><b>Hardware specifications</b></p> <p><b>Physical</b></p> <p>48 RJ45 ports of 1G, 4 SFP+ ports of 10G and 2 QSFP28 ports of 100G</p> <p>Out-of-band management port (10/100/1000BASE-T)</p> <p>USB (Type A) port for configuration via USB flash drive</p> <p>MicroUSB (Type B) console port (MicroUSB to USB connector cable included)</p> <p>RJ45 console port with RS232 signaling (RJ-45 to female DB-9 connector cable included)</p> <p>Auto-negotiation for speed and flow control</p> <p>Auto-MDI/MDIX, port mirroring</p> <p>Flow-based port mirroring Broadcast storm control</p> <p>Energy-Efficient Ethernet per port settings</p> <p>Redundant variable speed fans</p> <p>Air flow: Normal or Reverse Power supply: 550W 80PLUS. Optional 2nd PSU for redundancy</p> <p>Dual firmware images on-board</p> <p>Switching engine model: Store and forward</p> <p><b>Chassis</b></p> <p>Size (1U, H x W x D):            1.71 in x 17.09 in x 15.75 in            (43.5 mm x 434 mm x 400 mm). Power supply/ fan tray handle adds 1.18 in</p> <p>Weight: 15.4 lbs (6.99 kg); PSU 1.75 lbs (0.79 kg)—550 W</p> <p>2-post rack mounting kit</p>	<p><b>Environmental</b></p> <p>Power supply efficiency:            88% or better in all operating modes</p> <p>Maximum thermal output (BTU/hr): 349.06</p> <p>Power consumption max (watts): 212</p> <p>Operating temperature: 32° to 113°F            (0° to 45°C)</p> <p>Operating humidity: 5% to 95% (RH), noncondensing</p> <p>Storage temperature: –40°F to 149°F            (–40°C to 70°C))</p> <p>Storage relative humidity: 5% to 95%, noncondensing</p> <p><b>Performance</b></p> <p>CPU memory: 16GB DDR4</p> <p>Flash: 32GB SSD</p> <p>Packet buffer memory: 8MB</p> <p>Switch fabric capacity (half duplex): 288Gbps</p> <p>Forwarding rate: 800Mpps</p> <p>Line-rate Layer 2 switching: All (non-blocking) Line-rate Layer 3 routing: All (non-blocking)</p> <p>Number of VLANs per system: 4K</p> <p>Number of VLAN members per system: 4K</p> <p>Number of MAC addresses per system: 8K</p> <p><b>Network Operating System specifications</b></p> <p>For Network Operating System (NOS) specific features, refer to <a href="#">Dell SmartFabric OS10 and Enterprise SONiC Distribution by Dell Technologies spec sheet</a></p>	<p><b>Regulatory, environment and other compliance</b></p> <p><b>Safety and emissions</b></p> <p>Australia/New Zealand: ACMA RCA</p> <p>Class A Canada: ICES Class A; cUL</p> <p>China: CCC Class A; NAL Europe: CE Class A Japan: VCCI Class A</p> <p>USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11</p> <p>Eurasia Customs Union: EAC Germany: GS mark</p> <p>Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China. For more country-specific regulatory information, and approvals, please see your Dell Technologies representative.</p> <p><b>Warranty</b></p> <p>1 year return to depot constrained</p> <p><b>RoHS</b></p> <p>Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell Technologies representative.</p> <p><b>EU WEEE</b></p> <p>EU Battery Directive REACH</p> <p><b>Energy</b></p> <p>Japan: JEL</p> 

## IT Lifecycle Services for Networking

### Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



#### Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



#### Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



#### Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell Networking technology and learn how to increase performance and optimize infrastructure.



#### Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



#### Optimize

Maximize performance for dynamic IT environments with Dell Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



#### Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at [DellTechnologies.com/Services](https://DellTechnologies.com/Services)



[Learn more](#)  
Dell Networking  
solutions



[Contact](#) a Dell  
Technologies Expert



[View more](#) resources



[Join the conversation](#)  
with #DellTechnologies

© 2024 Dell Inc. or its subsidiaries. All Rights Reserved. Dell and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.